



CENTURY 2000

Anhydrous Ammonia Hose N2000

APPLICATION AND KEY POINTS:

- Low-permeation, anhydrous ammonia transfer hose
- Developed for use with nurse tanks
- Distinctly identified with a bold green stripe
- Branded with removal date
- Prorated 6-year warranty for agricultural applications only, when coupled by an approved distributor

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 5:1

MATERIAL TUBE:

- Smooth, seamless extruded EPDM
- High heat resistance
- Low permeation

REINFORCEMENTS:

- Multiple high-tensile textile braids

MATERIAL COVER:

- Black EPDM
- Abrasion, weather, and ozone-resistant
- Pin-pricked to assist the resistance of cover blisters and promote better dissipation of the anhydrous ammonia

BRANDING:

- Green longitudinal mylar stripe: GOODALL® N2000 CENTURY 2000 • ANHYDROUS AMMONIA 350 PSI
- Embossed stripe: N2000 • ANHYDROUS AMMONIA • 350 PSI MAX W.P. * • FOR AG. SVC. • REMOVE HOSE BEFORE ** • REFER TO INDUSTRY RECOMMENDATIONS INCL RMA/IP-11-2 FOR CARE • 10001 • *** •

* Year of Manufacture

** Year of Manufacture plus 6 years

*** Year-Month of Manufacture

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
3/8	0.90	350	2.5	0.33
1/2	1.00	350	3.0	0.35
3/4	1.25	350	4.0	0.46
1	1.52	350	5.0	0.54
1 1/4	1.75	350	5.5	0.67
1 1/2	2.05	350	7.5	0.88
2	2.66	350	11.0	1.31

All data at 68° F