



RHINO

Hot Air Blower Hose N2497

APPLICATION AND KEY POINTS:

- Premium hose for conveying hot air from blower or compressor to tanks on dry bulk material carriers and on in-plant compressors to holding tanks
- Transfer hose of hot, non-oily air
- Heavy-duty construction

TEMPERATURE RANGE:

- -40°F to +375°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded EPDM
- High-temperature resistance

REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual steel helix wire for added stability and flexibility

MATERIAL COVER:

- Black EPDM
- Abrasion, weather, and ozone resistant
- Excellent heat resistance

BRANDING:

- Yellow spiral mylar stripe: GOODALL® N2497 RHINO • HOT AIR BLOWER 75 PSI
- Embossed stripe: N2497 • RHINO HOT AIR BLOWER • 75 PSI MAX WP • 375F MAX TEMP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
3	3.66	75	27	13.0	1.91
4	4.65	75	27	18.0	2.46

All data at 68° F

LAYLINE:  **N2497 RHINO • HOT AIR BLOWER**  