



GREY GUARDIAN

Washdown Hose

N2613

APPLICATION AND KEY POINTS:

- Designed for low-pressure steam applications
- Extremely flexible and resistant to kinking

TEMPERATURE RANGE:

- -40°F to +366°F

BURST PRESSURE:

- Water: Minimum 4:1
- Steam: Minimum 10:1

MATERIAL TUBE:

- Smooth, seamless extruded EPDM
- High heat resistance
- Low permeation

REINFORCEMENTS:

- Single high-tensile brass-plated steel wire braid
- Brass-plated wire provides excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Grey EPDM
- Pin-pricked to resist cover blistering
- Non-marking

BRANDING:

- White spiral mylar stripe: GOODALL[®] N2613 GREY GUARDIAN • WATER 300 PSI
- Embossed stripe: N2613 • GREY GUARDIAN • 150 PSI MAX WP STEAM • 300 PSI MAX WP WATER • * • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
3/4	1.19	300 (Water) 150 (Steam)	6.0	0.45

All data at 68° F

LAYLINE: **N2613 GREY GUARDIAN • WATER**