



BLUE DRAGON

Hydrocarbon Drain Hose

N2658

APPLICATION AND KEY POINTS:

- To drain hydrocarbons from the operation of steam cleaning vessels, tanks, and piping systems in the chemical and petrochemical industry
- Superior core that is crush and kink-resistant

TEMPERATURE RANGE:

- -40°F to +250°F (300°F intermittent)

BURST PRESSURE:

- Minimum 5:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Exceptional heat and oil resistance

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion
- Textile breaker yarn results in higher adhesion levels.

MATERIAL COVER:

- Blue Hypalon (CSM)
- Abrasion, oil, weather, and ozone resistant
- Excellent resistance to petroleum products and the effects of weathering
- Superior color-stay properties

BRANDING:

- Green longitudinal mylar stripe: GOODALL® N2658 BLUE DRAGON • HYDROCARBON DRAIN 300 PSI
- Embossed stripe: N2658 • BLUE DRAGON • HYDROCARBON DRAIN • 300 PSI MAX WP • 10001 •
- * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- ¾ and 1 inch: 50 feet
- 2 inch: 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
¾	1.20	300	4.0	0.44
1	1.57	300	5.0	0.74
2	2.58	300	10.0	1.50

All data at 68° F

LAYLINE:  **N2658 BLUE DRAGON • HYDROCARBON DRAIN**  