



NUTRALON SD GREY

Food Suction & Discharge Hose

N2708

APPLICATION AND KEY POINTS:

- Food suction and discharge hose for transfer of milk products, animal fat, vegetable oil, fruit juices, and other food products
- Suitable for alcohol 96% at 104°F (intermittent at 208°F - 30 minutes)
- For tank truck or in-plant service
- Braided construction has excellent flexibility and resistance to kinking
- Improved ergonomics for operators
- Complies with multiple international regulations including 3A (18.3 CLASSII), USDA, FDA, BFR and EC 1935/2004
- Easy to clean because of the smooth tube
- ADI (Animal Derived Ingredient) Free
- Phthalate-free
- Non-marking abrasion-resistant cover

TEMPERATURE RANGE:

- -22°F to 212°F
- Open end steam cleaning up to 266°F (max 20 minutes)

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- White, smooth, seamless extruded nitrile (NBR)
- Non-contaminating formulation

- Complies to the most stringent international food regulations
- Excellent resistance to fatty foods like animal fats and vegetable oils
- Does not propagate bacteria growth
- Excellent resistance to the most common cleaning agents

REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual steel helix wire for added stability and flexibility

MATERIAL COVER:

- Grey neoprene (CR)
- Superior abrasion, weather, and ozone resistance
- Resistant to vegetable oils and animal fats
- Non-marking

BRANDING:

- White and red spiral mylar stripe: GOODALL® N2708 NUTRALON SD • FOOD 10 BAR – 150 PSI
- Embossed stripe: NUTRALON SD • DN * • 10 BAR-150 PSI • MEETS FDA, BFR, EC 1935/2004, 3A 18-03 CLASS II & USDA REQS • MFR C-Y-M • MADE IN CANADA 10001

* DN size

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
1	1.46	150	27	6.0	0.57
1 ½	2.01	150	27	8.0	0.83
2	2.60	150	27	9.0	1.50
3	3.58	150	27	13.0	2.42

All data at 68° F