



ELEPHANT HIDE

LPG Hose

N2804

APPLICATION AND KEY POINTS:

- Premium LPG transfer hose for demanding conditions
- Compatible with propane, butane, and natural gas for use in well-ventilated areas
- ATTENTION! Not to exceed 20 psi max working pressure when used for natural gas transfer
- Exceptionally high abrasion-resistant cover
- Ideal for tank truck service and trailer to storage use
- Approved to UL 21 specifications

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 5:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG

REINFORCEMENTS:

- Multiple high-tensile textile braids

MATERIAL COVER:

- Black neoprene (CR)
- Superior abrasion resistance
- Formulated to resist cracking from exposure to weather and ozone conditions
- Pin-pricked to resist cover blistering

BRANDING:

- Yellow and blue spiral mylar stripe: GOODALL® N2804 ELEPHANT HIDE • LPG 350 PSI
- Embossed stripe: N2804 • ELEPHANT HIDE • MH8393 • LP GAS HOSE ISSUE NO E8073 • * • 350 PSI (2.4 Mpa) • • MAX WP • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1	1.56	350	5.0	0.65
1 ¼	1.83	350	6.0	0.87
2	2.71	350	10.0	1.39

All data at 68° F

LAYLINE: **N2804 ELEPHANT HIDE • LPG**