

ELEPHANT HIDE PLUS

LPG Hose N2805

APPLICATION AND KEY POINTS:

- Superior LPG transfer hose for demanding conditions
- Compatible with propane, butane, and natural gas for use in well-ventilated areas
- Reinforced with corrosion-resistant stainless steel braids
- Exceptional high abrasion-resistant cover
- Ideal for tank truck service and trailer-to-storage use
- Approved to UL 21 specifications

TEMPERATURE RANGE:

-40°F to +180°F

BURST PRESSURE:

• Minimum 5:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG

REINFORCEMENTS:

- Multiple high-tensile stainless steel wire braids
- Stainless steel wires provide excellent corrosion resistance
- Single high-tensile textile braid

MATERIAL COVER:

- Black neoprene (CR)
- Superior abrasion resistance
- Formulated to resist cracking from exposure to weather and ozone conditions
- Pin-pricked to resist cover blistering

BRANDING:

- Yellow, black and blue spiral mylar stripe: GOODALL® N2805 ELEPHANT HIDE PLUS • LPG 350 PSI
- Embossed stripe: N2805 ELEPHANT HIDE PLUS MH8393 N LP GAS HOSE ISSUE NO E8073 * 350 PSI (2.4 Mpa) MAX WP 10001 REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

100 feet

TECHNICAL SPECIFICATIONS				
ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1	1.62	350	4.0	0.88
1 1/4	1.87	350	6.0	1.05
1 1/2	2.12	350	7.5	1.25
2	2.70	350	9.0	1.85
3	3.88	350	18.0	3.50

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES. EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer/s/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance, and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental, and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.

All data at 68° F

^{*} Year - Month