



AIR KING

General Purpose Air Hose
 N2844-1 - Black Cover
 N2844 - Yellow Cover

APPLICATION AND KEY POINTS:

- Medium-duty compressed air hose for use in construction sites
- Robust construction that is kink-resistant but still flexible
- Developed for the transfer of high-temperature air
- May be used as a tough water transfer hose

TEMPERATURE RANGE:

- -40°F to +268°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Exceptional heat and oil resistance

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Black or yellow styrene-butadiene (SBR)
- Excellent abrasion, weather, and ozone resistance
- Pin-pricked to resist cover blistering

BRANDING:

- Blue longitudinal mylar stripe: GOODALL® N2844 AIR KING • AIR 500 PSI 268°F
- Embossed stripe: N2844 • AIR KING • 500 PSI MAX WP • 268°F MAX TEMP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
3	3.62	500	12.5	2.81

All data at 68° F