# **ARCTIC BLUE FOX**



#### APPLICATION:

- Suction and discharge hose for the transfer of petroleum-based products such as gasoline, oil and diesel
- Constructed for in-plant use or tank truck
- Flexibility maintained in extreme cold temperatures
- Full vacuum rating

## **TEMPERATURE RANGE:**

- -65°F to +200°F
- -54°C to +95°C

## **BURST PRESSURE:**

Minimum 4:1

#### **MATERIAL TUBE:**

- Extruded, smooth superior nitrile (NBR) compound
- Designed to withstand extreme cold temperatures

#### REINFORCEMENTS:

- Multiple braids of high-tensile textile
- Dual-wire helix for stability and added flexibility

## MATERIAL COVER:

- Blue, smooth neoprene (CR) compound
- Vibrant blue color for high visibility
- Excellent resistance to weather, ozone and petroleum based products

#### **BRANDING:**

- Red longitudinal mylar stripe: GOODALL® ARCTIC BLUE FOX • PETROLEUM 150 PSI
- Embossed stripe: N2675 • ARCTIC BLUE FOX • -65° F TO +200° F TEMP • 150 PSI MAX WP • \* • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

#### STANDARD LENGTH:

- 100 feet
- 30.5 meters

### **ARCTIC BLUE FOX**

ID		OD		maximum working pressure		vacuum	minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	hg	mm	inch	kg/m	lb./ft.
38.0	1 ½	55.1	2.17	10	150	28	114.3	4.5	1.52	1.02
51.0	2	66.0	2.60	10	150	28	177.8	7.0	1.90	1.28
63.0	2 ½	80.8	3.18	10	150	28	254.0	10.0	2.60	1.75
76.0	3	93.5	3.68	10	150	28	279.4	11.0	3.07	2.06
102.0	4	121.9	4.80	10	150	28	355.6	14.0	4.73	3.18
All data at 68° F / 20° C										

ARCTIC BLUE FOX • PETROLEUM 150 PSI



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer/s/user/s method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.