# **BLACK DRAGON**



### APPLICATION:

- Delivery hose for the transfer of hot tar and asphalt
- Ideal for use as a wand hose or crack sealer melter and applicator
- Extremely flexible and kinkresistant construction

## TEMPERATURE RANGE:

- -40°F to +350°F (400°F intermittent)
- -40°C to +175°C (205°C intermittent)

# BURST PRESSURE:

■ Minimum 4:1

### **MATERIAL TUBE:**

 Extruded, smooth heat-resistant neoprene (CR) compound

### REINFORCEMENTS:

- Multiple braids of high-tensile wire
- Braided with brass plated wire for corrosion resistance

### MATERIAL COVER:

- Black, smooth neoprene (CR) rubber
- Designed with superior heat and oil resistance
- Excellent weather and ozone resistance

### **BRANDING:**

- Red spiral mylar stripe:
  GOODALL® BLACK DRAGON
  - CRACK SEALER 300PSI
- Embossed stripe: N2533
  BLACK DRAGON CRACK
  SEALER SERVICE ONLY •
  WP 300 PSI MAX 10001
  - \* REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

# STANDARD LENGTH:

- ¾ inch and 1 inch: 250 feet, 76.2 meters
- 1 ½ inches: 100 feet, 30.5 meters

# **BLACK DRAGON**

ID		OD		maximum working pressure		minimum bend radius		v	weight	
mm	inch	mm	inch	bar	psi	mm	inch	kg/m	lb./ft.	
19.0	3/4	30.0	1.18	21	300	76.2	3.0	0.70	0.47	
25.0	1	39.4	1.55	21	300	101.6	4.0	1.24	0.83	
38.0	1 1/2	52.1	2.05	21	300	203.2	8.0	1.59	1.07	
All data at 6	58° F / 20° C									

ETT BLACK DRAGON • CRACK SEALER 300 PSI ■

