



## PULP KING

### APPLICATION :

- Heavy-duty wash down and cleaning applications, using cold and warm water up to 180°F / 82°C
- The weather, abrasion and heat resistant cover guarantees a longer lifetime compared to competitor products.
- Extreme flexibility and kink resistance
- The ideal solution for the pulp & paper and mining industry

### TEMPERATURE RANGE :

- -40°F to +180°F
- -40°C to +82°C

### BURST PRESSURE:

- Minimum 4:1

### MATERIAL TUBE :

- Extruded, smooth high-grade SBR rubber

### REINFORCEMENTS :

- Multiple high-tensile textile braids

### MATERIAL COVER :

- Black, smooth SBR rubber
- Excellent weather and ozone resistance

### BRANDING:

- Red and yellow spiral mylar stripe : GOODALL® PULP KING - WATER 300PSI
- Embossed stripe: N501 • PULP KING • 300 PSI MAX WP • \* • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

### STANDARD LENGTHS:

- 100 feet, 30.5 meters

## PULP KING

ID		OD		maximum working pressure		minimum burst pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb./ft.
12,7	1/2"	30.5	1.20	21,0	300	84	1200	63,5	2,5	0,73	0,49
19,0	3/4"	35.6	1.40	21,0	300	84	1200	88,9	3,5	0,91	0,61
25,0	1"	41.9	1.65	21,0	300	84	1200	114,3	4,5	1,06	0,71
32,0	1.1/4"	50.0	1.97	21,0	300	84	1200	152,4	6,0	1,25	0,84
38,0	1.1/2"	54.6	2.15	21,0	300	84	1200	165,1	6,5	1,47	0,99
51,0	2"	67.3	2.65	21,0	300	84	1200	228,6	9,0	1,87	1,26

All data at 68°F/20°C

