

# FLEXTUBE DRY CEMENT HOSE

## Dry Cement Discharge Hose N2496

### APPLICATION AND KEY POINTS:

- For discharge of dry powdered cement or powdered lime from bulk pneumatic trailers
- Static conductive tube

### TEMPERATURE RANGE:

- -20°F to +180°F

### BURST PRESSURE:

- Minimum 4:1

### MATERIAL TUBE:

- 1/8 smooth, seamless extruded styrene-butadiene (SBR)
- Abrasion-resistant
- Static conductive

### REINFORCEMENTS:

- Single high-tensile textile braid

### MATERIAL COVER:

- Black styrene-butadiene (SBR)
- Excellent abrasion, weather, and ozone resistance

### BRANDING:

- Green longitudinal mylar stripe: GOODALL<sup>®</sup> N2496 FLEXTUBE DRY CEMENT 100 PSI MAX W.P. MADE IN CANADA 10001 REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE
- Embossed stripe: MFR C-Y-M

### STANDARD LENGTHS:

- 100 feet

## TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
4	4.44	100	7	1.29

All data at 68° F