



WEAR KING

Dry Material Discharge Hose N2498

APPLICATION AND KEY POINTS:

- Discharge of sand, pebble lime, or other highly abrasive dry materials
- ¼ inch thick tube to ensure a longer hose life
- Conductive tube to ensure safe handling

TEMPERATURE RANGE:

- -20°F to +180°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- ¼ inch black, smooth, seamless extruded, static conductive EPDM
- High abrasion resistance

REINFORCEMENTS:

- Single high-tensile textile braid

MATERIAL COVER:

- Black styrene-butadiene (SBR)
- Abrasion, weather, and ozone-resistant

BRANDING:

- White spiral mylar stripe: GOODALL[®] N2498 WEAR KING • SAND DISCHARGE 75 PSI
- Embossed stripe: N2498 • WEAR KING • 75 PSI MAX WP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE •

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
4	4.76	75	42.5	2.63

All data at 68° F

LAYLINE:  **N2498 WEAR KING • SAND DISCHARGE**  