

# HYDROGEN CYANIDE N2524

## APPLICATION AND KEY POINTS:

- Specifically designed for hydrogen cyanide service

## TEMPERATURE RANGE:

- -40°F to +180°F

## BURST PRESSURE:

- Minimum 10:1

## MATERIAL TUBE:

- Black smooth, seamless extruded Hypalon (CSM)
- HCN resistant

## REINFORCEMENTS:

- Multiple high-tensile stainless steel wire braids
- Stainless steel wires provide excellent corrosion resistance
- Dual steel helix wire for added stability and flexibility

## MATERIAL COVER:

- Yellow Hypalon (CSM)
- Weather and ozone resistant
- High visibility

## BRANDING:

- Yellow spiral mylar stripe: GOODALL<sup>®</sup> N2524 HYDROGEN CYANIDE 125 PSIG MAX W.P. 188 PSIG TEST MADE IN CANADA 1001 REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE
- Embossed stripe: MFR C-Y-M MO# \*\*\*\*\*

*MO number to match the floor order number*

## STANDARD LENGTHS:

- 100 feet

## TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
2	2.88	125	27	10	2.85

All data at 68° F