

CROCODILE

Water Suction Hose

N2582

APPLICATION AND KEY POINTS:

- Heavy-duty water suction hose for use in quarries on large construction projects or other areas where an extra rugged heavy-duty cover hose is required

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 4:1 Safety Factor

MATERIAL TUBE:

- Smooth, seamless extruded EPDM
- High heat resistance

REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual steel helix wire for added stability and flexibility

MATERIAL COVER:

- Black EPDM
- Abrasion, weather, and ozone resistant

BRANDING:

- Yellow longitudinal stripe
- Embossed Stripe: GOODALL[®] N2582 • CROCODILE WATER SUCTION • 250 PSI MAX WP • MFR C-Y-M • MADE IN CANADA 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE •

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
2	2.53	250	27	6.5	1.05

All data at 68° F