ROCK BREAKER PLUS

Heavy Duty Air Hose N2705

APPLICATION AND KEY POINTS:

- Heavy-duty multi-purpose air hose for use in industrial, construction and mining applications
- · Extremely flexible and kink-resistant

TEMPERATURE RANGE:

• -40°F to +200°F

BURST PRESSURE:

Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)/styrenebutadiene (SBR) blend
- · Heat and oil-resistant

REINFORCEMENTS:

Multiple high-tensile textile braids

MATERIAL COVER:

- Yellow styrene-butadiene (SBR)
- Excellent abrasion, weather, and ozone resistance

BRANDING:

- Yellow longitudinal mylar stripe: GOODALL® N2705 ROCK BREAKER AIR * PSI MAX W.P. MADE IN CANADA 10001 REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE
- Embossed Stripe: MFR C-Y-M

STANDARD LENGTHS:

100 feet

TECHNICAL SPECIFICATIONS				
ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1	1.51	400	3	0.56
1 1/2	2.00	400	9	0.79
2	2.56	400	10.5	1.04
All data at 68° F				

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES. EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, instillation, care, maintenance, and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental, and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.

^{*} Maximum working pressure