



SUPER KEMFLEX

Chemical Suction & Discharge Hose

N2718

APPLICATION AND KEY POINTS:

- Suitable for chemical transfer in chemical plants, ships, barge and tank truck service
- Light and extremely flexible
- Superior kink and crush resistance
- Lighter weight due to the monofilament helix
- Can be open end steam cleaned (max 30 minutes at 266°F)

TEMPERATURE RANGE:

- -40°F to +180°F
- May be used intermittently to 212°F depending on product being transferred

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Clear ultra-high molecular weight polyethylene (UHMWPE)
- Resistant to 95% of chemicals in the industry
- Uses FDA compliant materials

REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual monofilament helix wire for added stability and flexibility
- Constructed with anti-static wires

MATERIAL COVER:

- Green EPDM
- Abrasion, weather, and ozone resistant

BRANDING:

- Yellow longitudinal mylar stripe: GOODALL® N2718 SUPER KEMFLEX • CHEMICAL 200 PSI
- Embossed stripe: N2718 • SUPER KEMFLEX • 200 PSI MAX WP • 180°F MAX TEMP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

* Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
1	1.60	200	27	4.0	0.55
1 ¼	1.84	200	27	5.0	0.68
1 ½	2.09	200	27	6.0	0.79
2	2.60	200	27	7.0	1.01
3	3.74	200	27	10.0	1.89

All data at 68° F