

FIBERGLASS STEAM N2774

APPLICATION AND KEY POINTS:

- All steam and hot water/steam applications where a non-conductive tube, superior life, safety and performance are important
- Special EPDM cover provides substantially longer service life due to its heat age resistance

TEMPERATURE RANGE:

- -40°F to +450°F

BURST PRESSURE:

- Minimum 10:1

MATERIAL TUBE:

- Smooth, seamless extruded chlorobutyl (CIIR)
- Excellent resistance to popcorning and blistering

REINFORCEMENTS:

- Multiple Fiberglass Braids

MATERIAL COVER:

- Red EPDM
- Excellent abrasion, weather, and ozone resistance
- Pin-pricked to resist cover blistering

BRANDING:

- Embossed stripe: N2774 FIBREGLASS STEAM 250 PSI MAX WP 450° F MAX TEMP CAUTION TIGHTEN CLAMPS BEFORE USING MADE IN CANADA 10001 REFER TO INDUSTRY RECOMMENDATIONS MFR-C-***

*** Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
3/4	1.44	250	4	0.60

All data at 68° F