



PETRALL FLEX PETROLEUM

Petroleum Transfer Hose N2827

APPLICATION AND KEY POINTS:

- Petroleum transfer used in tank truck and in-plant service to transfer oil and other petroleum base products
- Superior crush resistance with excellent 'rebound' characteristics
- Light and flexible
- Hose construction gives excellent bend radius

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Excellent oil resistance

REINFORCEMENTS:

- Multiple high-tensile textile braids
- Dual monofilament helix for added stability and flexibility
- Anti-static wire

MATERIAL COVER:

- Black nitrile (NBR)
- Abrasion, oil, weather, and ozone-resistant

BRANDING:

- Orange longitudinal mylar stripe: GOODALL® N2827 PETRALL FLEX PETROLEUM 200 PSI Max W.P. MADE IN CANADA 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE
- Embossed stripe: MFR C-Y-M

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Vacuum (inHg)	Min BR (in)	Weight (lb/ft)
2	2.64	200	27	7	1.20

All data at 68° F

LAYLINE:  **N2827 PETRALL FLEX • PETROLEUM**