



FRACTURING DISCHARGE N2865

APPLICATION AND KEY POINTS:

- Transfer of fracturing products
- Extremely durable for harsh environments

TEMPERATURE RANGE:

- -40°F to +180°F

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Abrasion-resistant

REINFORCEMENTS:

- Multiple high-tensile brass-plated steel wire braids
- Brass-plated wires provide excellent corrosion resistance and improved adhesion

MATERIAL COVER:

- Superior abrasion-resistant "Elephant Hide" black neoprene (CR)
- Formulated to resist cracking from exposure to weather and ozone conditions

BRANDING:

- Yellow spiral mylar stripe
- GOODALL® ELEPHANT HIDE N2865 400 PSI MAX W.P. MADE IN CANADA 10001 MFR C-*** REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE AND MAINTENANCE

*** Year - Month

STANDARD LENGTHS:

- 100 feet

TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
4	4.56	400	20	3.13

All data at 68° F