



# IMPACT LPG

LPG Hose  
N372A-2

### APPLICATION AND KEY POINTS:

- For transferring LPG and natural gas in bulk storage and bulk truck service
- Compatible with propane, butane, and natural gas for use in well-ventilated areas
- ATTENTION! Not to exceed 20 psi max working pressure when used for natural gas transfer
- Light and flexible
- Approved to UL 21 specifications

### TEMPERATURE RANGE:

- -40°F to +180°F

### BURST PRESSURE:

- Minimum 5:1

### MATERIAL TUBE:

- Smooth, seamless extruded nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG

### REINFORCEMENTS:

- Multiple high-tensile textile braids

### MATERIAL COVER:

- Black neoprene (CR)
- Excellent abrasion, weather, and ozone resistance
- Moderate resistance to oils and fuels
- Pin-pricked to resist cover blistering

### BRANDING:

- Embossed stripe: GOODALL MH8393 N372A  L.P. GAS HOSE ISSUE NO. E8073 MAZ W.P. 350 PSIG (2.4 MPa) • \* • MADE IN CANADA 10001 REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE

\* Year - Month

### STANDARD LENGTHS:

- 100 feet

## TECHNICAL SPECIFICATIONS

ID (in)	OD (in)	Max WP (psi)	Min BR (in)	Weight (lb/ft)
1 ¼	1.87	350	12	0.94
1 ½	2.11	350	14	1.03
2	2.65	350	16	1.25

All data at 68° F