



HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER: Goodall Rubber
 Registered to ISO 9001:2008 Quality Management System
 (File number 000593) & ISO 14001:2004 Environmental
 Management System (File number 000593)

HOSE TYPE: WORK OVER RIG

SPECIFICATION: N1253

SIZE: 2" - 3"

HOSE DIMENSIONS

ID (inches):	2"	2 1/2"	3"
OD (inches):	2.74"	3.37"	3.86"
MINIMUM BEND RADIUS (inches):	9.50"	10.50"	15"
LENGTH (feet) AVAILABLE:	100'	100'	100'

HOSE DESIGN

TUBE: Neoprene

REINFORCEMENT: High Tensile Wire Braids

COVER: Black Neoprene

STRIPE: Yellow Longitudinal

BRANDING: Goodall N1253 Work Over Rig Liquid Service 2000 PSI Max W.P.
 Air/Gas Service 1000 PSI Max W.P.
 Made in Canada 10001
 Refer to Industry Recommendations for Proper Care & Maintenance

SPECIFICATION

MAXIMUM WP: 1000 PSI Max W.P. Air/Gas
 2000 PSI Max W.P. Liquid

SAFETY RATIO: 4:1 Minimum

TEMPERATURE RANGE: -40°F to 268°F For Air Service Only
 -40°F to 180°F For Oil Service

Notes: _____

Prepared By: Monika McKean

Released By: Monika McKean

Issue Date: 4/28/23

Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.

Contact your local Eriks division for any questions.