



# HOSE DATA SHEET

## GENERAL INFORMATION

**MANUFACTURER:** Goodall Rubber Co. of Canada LP  
 Registered to ISO 9001:2008 Quality Management System  
 (File number 000593) & ISO 14001:2004 Environmental  
 Management System (File number 000593)

**HOSE TYPE:** PETROFLO PETROLEUM PETRO FLEX TANK TRUCK

**SPECIFICATION:** N2490

**SIZE:** 1" - 4"

## HOSE DIMENSIONS

<b>ID (inches):</b>	1"	1 1/2"	2"	2 1/2"	3"	4"
<b>OD (inches):</b>	1.54"	2.07"	2.57"	3.10"	3.66"	4.70"
<b>MINIMUM BEND RADIUS (inches):</b>	3"	6"	7"	9"	10"	13"
<b>LENGTH (feet) AVAILABLE:</b>	100'	100'	100'	100'	100'	100'

## HOSE DESIGN

**TUBE:** High Grade Oil Resistant Nitrile

**REINFORCEMENT:** Multiple Braid of High Tensile Textile With Dual Steel Helix Wire

**COVER:** Tan Abrasion, Oil, Weather & Ozone Resistant Hypalon

**STRIPE:** Double Green Stripe

**BRANDING:** Goodall N2490 Petroflow Petroleum 150 PSI Max W.P.  
 Made in Canada 10001  
 Refer to Industry Recommendations for Proper Care & Maintenance

## SPECIFICATION

**MAXIMUM WP:** 150 PSI W.P.

**SAFETY RATIO:** 4:1 Minimum

**TEMPERATURE RANGE:** -40°F to 180°F

**Notes:** \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Prepared By:** Jason Whiteside

**Released By:** Laura Bishop

**Issue Date:** 05/05/2016

*Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.*

*Contact your local Eriks or Lewis-Goetz Co division for any questions.*