



HOSE DATA SHEET

GENERAL INFORMATION

MANUFACTURER: Goodall Rubber Co. of Canada LP
 Registered to ISO 9001:2008 Quality Management System
 (File number 000593) & ISO 14001:2004 Environmental
 Management System (File number 000593)

HOSE TYPE: PAPERMILL WASHDOWN WITH NOZZLE

SPECIFICATION: N2593

SIZE: 1" - 1 1/4"

HOSE DIMENSIONS

ID (inches):	1"	1 1/4"
OD (inches):	1.47"	1.72"
MINIMUM BEND RADIUS (inches):	5"	6"
LENGTH (feet) AVAILABLE:	50'	50'-100'

HOSE DESIGN

TUBE: SBR

REINFORCEMENT: High Tensile Textile Braids

COVER: Black SBR

STRIPE: White Spiral

BRANDING: Goodall N2593 Papermill Washdown 300 PSI Max W.P.
 Refer to Industry Recommendations for Proper Care & Maintenance
 Made in Canada 10001

SPECIFICATION

MAXIMUM WP: 300 PSI W.P.

SAFETY RATIO: 4:1 Minimum

TEMPERATURE RANGE: -40°F to 180°F

Notes: _____

Prepared By: Jason Whiteside

Released By: _____

Issue Date: _____

Prior to use, refer to RMA and other industry chemical resistance references for chemical and temperature compatibility.

Contact your local Eriks or Lewis-Goetz Co division for any questions.