



WEAR KING

APPLICATION:

- Discharge of sand, pebble lime or other highly abrasive dry materials
- 1/4 inch thick tube to ensure a longer hose life
- Conductive tube to ensure safe handling

TEMPERATURE RANGE:

- -20°F to +180°F
- -29°C to +82°C

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- 1/4 inch High Grade abrasion resistant and static conductive SBR/NR tube

REINFORCEMENTS:

- High-tensile textile braid

MATERIAL COVER:

- Black abrasion, weather, and ozone resistant SBR

BRANDING:

- White spiral mylar stripe: GOODALL • WEAR KING • SAND DISCHARGE 75 PSI
- Embossed stripe: N2498 • WEAR KING • 75 PSI MAX WP • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

- 100 feet, 30.5 meters

WEAR KING

ID		OD		maximum working pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	mm	inch	kg/m	lb./ft.
76.0	3	94.7	3.73	5	75	-	-	2.87	1.93
102.0	4	120.9	4.76	5	75	-	-	3.73	2.51

All data at 68° F / 20° C



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.